

# **siunitx** – A comprehensive (SI) units package\*

Joseph Wright<sup>†</sup>

Released 2018-07-21

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Using the <code>siunitx</code> package</b>	<b>2</b>
2.1	Numbers . . . . .	2
2.2	Angles . . . . .	3
2.3	Units . . . . .	3
2.4	The unit macros . . . . .	4
2.5	Unit abbreviations . . . . .	7
2.6	Tabular material . . . . .	10
<b>3</b>	<b>Package control options</b>	<b>12</b>
3.1	The key–value control system . . . . .	12
3.2	Printing . . . . .	13
3.3	Parsing numbers . . . . .	15
3.4	Post-processing numbers . . . . .	16
3.5	Printing numbers . . . . .	20
3.6	Angles . . . . .	22
3.7	Using units . . . . .	24
3.8	Tabular material . . . . .	27
<b>4</b>	<b>Installation</b>	<b>36</b>
<b>5</b>	<b>Thanks</b>	<b>36</b>
<b>6</b>	<b>Making suggestions and reporting bugs</b>	<b>37</b>

---

\*This file describes v3.0.0-alpha, last revised 2018-07-21.

<sup>†</sup>E-mail: joseph.wright@morningstar2.co.uk

### Abstract

Physical quantities have both numbers and units, and each physical quantity should be expressed as the product of a number and a unit. Typesetting physical quantities requires care to ensure that the combined mathematical meaning of the number–unit combination is clear. In particular, the SI units system lays down a consistent set of units with rules on how these are to be used. However, different countries and publishers have differing conventions on the exact appearance of numbers (and units). The `siunitx` package provides a set of tools for authors to typeset quantities in a consistent way. The package has an extended set of configuration options which make it possible to follow varying typographic conventions with the same input syntax. The package includes automated processing of numbers and units, and the ability to control tabular alignment of numbers.

## 1 Introduction

The correct application of units of measurement is very important in technical applications. For this reason, carefully-crafted definitions of a coherent units system have been laid down by the *Conférence Générale des Poids et Mesures* (CGPM): this has resulted in the *Système International d’Unités* (SI). At the same time, typographic conventions for correctly displaying both numbers and units exist to ensure that no loss of meaning occurs in printed matter.

The `siunitx` package aims to provide a unified method for L<sup>A</sup>T<sub>E</sub>X users to typeset numbers and units correctly and easily. The design philosophy of `siunitx` is to follow the agreed rules by default, but to allow variation through option settings. In this way, users can use `siunitx` to follow the requirements of publishers, co-authors, universities, *etc.* without needing to alter the input at all.

## 2 Using the `siunitx` package

### 2.1 Numbers

`\num`

`\num[<options>]{<number>}`

Numbers are automatically formatted by the `\num` macro. This takes one optional argument, `<options>`, and one mandatory one, `<number>`. The contents of `<number>` are automatically formatted. The formatter removes both “soft” (`\_`) and “hard” spaces (`\,` and `\~`), automatically identifies exponents (as standard marked using `e`, `E`, `d` or `D`) and adds the appropriate spacing of large numbers. With the standard settings a leading zero is added before a decimal marker, if needed: both `.` and `,` are recognised as decimal markers.

123	<code>\num{123}</code>	<code>\\\</code>
1 234	<code>\num{1234}</code>	<code>\\\</code>
12 345	<code>\num{12345}</code>	<code>\\\</code>
0.123	<code>\num{0.123}</code>	<code>\\\</code>
0.123 4	<code>\num{0,1234}</code>	<code>\\\</code>
0.123 45	<code>\num{.12345}</code>	<code>\\\</code>
$3.45 \times 10^{-4}$	<code>\num{3.45d-4}</code>	<code>\\\</code>
$-10^{10}$	<code>\num{-e10}</code>	

Note that numbers are parsed before typesetting, which does have a performance overhead (only obvious with very large amounts of numerical input). The parser understands a range of input syntaxes, as demonstrated above.

## 2.2 Angles

\ang

\ang[*options*]{*angle*}

Angles can be typeset using the \ang command. The *angle* can be given either as a decimal number or as a semi-colon separated list of degrees, minutes and seconds, which is called “arc format” in this document. The numbers which make up an angle are processed using the same system as other numbers.

$10^\circ$	\ang{10} \\
$12.3^\circ$	\ang{12.3} \\
$4.5^\circ$	\ang{4,5} \\
$1^\circ 2' 3''$	\ang{1;2;3} \\
$1''$	\ang{;;1} \\
$10^\circ$	\ang{+10;;} \\
$-0^\circ 1'$	\ang{-0;1;}

## 2.3 Units

\unit

\unit[*options*]{*unit*}

The symbol for a unit can be typeset using the \unit macro: this provides full control over output format for the unit. Like the \num macro, \unit takes one optional and one mandatory argument. The unit formatting system can accept two types of input. When the *unit* contains literal items (for example letters or numbers) then siunitx converts . and ~ into inter-unit product and correctly positions sub- and superscripts specified using \_ and ^. The formatting methods will work with both math and text mode.

$\text{kg m/s}^2$	\unit{\text{kg}.\text{m}/\text{s}^2} \\
$\text{g}_{\text{polymer}} \text{mol}_{\text{cat}} \text{s}^{-1}$	\unit{\text{g}_{\{\text{polymer}\}}\text{-}\text{mol}_{\{\text{cat}\}}.\text{s}^{-1}}

The second operation mode for the \unit macro is an “interpreted” system, Here, each unit, SI multiple prefix and power is given a macro name. These are entered in a method very similar to the reading of the unit name in English.

```
\unit{\kilo\gram\metre\per\square\second} \\
\unit{\gram\per\cubic\centi\metre} \\
\unit{\square\volt\cubic\lumen\per\farad} \\
\unit{\metre\squared\per\gray\cubic\lux} \\
\unit{\henry\second} \\
\kg\ms^{-2} \\
\g\cm^{-3} \\
\text{V}^2\text{l m}^3\text{F}^{-1} \\
\text{m}^2\text{Gy}^{-1}\text{lx}^3 \\
\text{Hs}
```

On its own, this is less convenient than the direct method, although it does use meaning rather than appearance for input. However, the package allows you to define new unit macros; a large number of pre-defined abbreviations are also supplied. More importantly, by defining macros for units, instead of literal input, new functionality is made available. By altering the settings used by the package, the same input can yield a variety of different output formats. For example, the `\per` macro can give reciprocal powers, slashes or be used to construct units as fractions.

`\qty`

```
\qty[<options>]{<number>}{<unit>}
```

Very often, numbers and units are given together. Formally, the value of a quantity is the product of the number and the unit, the space being regarded as a multiplication sign [5]. The `\qty` macro combines the functionality of `\num` and `\unit`, and makes this both possible and easy. The `<number>` and `<unit>` arguments work exactly like those for the `\num` and `\unit` macros, respectively.

```
\qty[mode = text]{1.23}{J.mol^{-1}.K^{-1}}          \\
\qty{.23e7}{\candela}                                \\
\qty[per-mode = symbol]{1.99}{\per\kilogram}        \\
\qty[per-mode = fraction]{1,345}{\coulomb\per\mole} \\
1.23 J mol-1 K-1                            \\
0.23 × 107 cd                                 \\
1.99 1/kg                                         \\
1.345  $\frac{\text{C}}{\text{mol}}$ 
```

It is possible to set up the unit macros to be available outside of the `\qty` and `\unit` functions. This is not the standard behaviour as there is the risk of name clashes (for example, `\bar` is used by other packages, and several packages define `\degree`). Full details of using “stand alone” units are found in ??.

## 2.4 The unit macros

The package always defines the basic set of SI units with macro names. This includes the base SI units, the derived units with special names and the prefixes. A small number of powers are also given pre-defined names. Full details of units in the SI are available on-line [1].

`\meter`

The seven base SI units are always defined (Table 1). In addition, the macro `\meter` is available as an alias for `\metre`, for users of US spellings. The full details of the base units are given in the SI Brochure [2].

The SI also lists a number of units which have special names and symbols [3]: these are listed in Table 2.

`\percent`

In addition to the official SI units, `siunitx` also provides macros for a number of units which are accepted for use in the SI although they are not SI units. Table 3 lists the “accepted” units [7]. Some units are fundamental physical quantities, and these are non-SI but can be used within the SI (Table 4, [8]). There are also a set of non-SI units which are used in certain defined circumstances (Table 5), although they are not necessarily officially sanctioned [9]. Finally, for specialist applications, a range of CGS units are sanctioned (Table 6) [10]. The command `\percent` is also provided for use in units: this is accepted with the SI as detailed in Section 5.3.7 of the Brochure [6].

`\deka`

In addition to the units themselves, `siunitx` provides pre-defined macros for all of the

Table 1: SI base units.

Unit	Command	Symbol
ampere	<code>\ampere</code>	A
candela	<code>\candela</code>	cd
<code>\kelvin</code>	K	
kilogram	<code>\kilogram</code>	kg
metre	<code>\metre</code>	m
mole	<code>\mole</code>	mol
second	<code>\second</code>	s

Table 2: Coherent derived units in the SI with special names and symbols.

Unit	Command	Symbol	Unit	Command	Symbol
becquerel	<code>\becquerel</code>	Bq	newton	<code>\newton</code>	N
degree Celsius	<code>\degreeCelsius</code>	°C	ohm	<code>\ohm</code>	Ω
coulomb	<code>\coulomb</code>	C	pascal	<code>\pascal</code>	Pa
farad	<code>\farad</code>	F	radian	<code>\radian</code>	rad
gray	<code>\gray</code>	Gy	siemens	<code>\siemens</code>	S
hertz	<code>\hertz</code>	Hz	sievert	<code>\sievert</code>	Sv
henry	<code>\henry</code>	H	steradian	<code>\steradian</code>	sr
joule	<code>\joule</code>	J	tesla	<code>\tesla</code>	T
lumen	<code>\lumen</code>	lm	volt	<code>\volt</code>	V
katal	<code>\katal</code>	kat	watt	<code>\watt</code>	W
lux	<code>\lux</code>	lx	weber	<code>\weber</code>	Wb

Table 3: Non-SI units accepted for use with the International System of Units.

Unit	Command	Symbol
day	<code>\day</code>	d
degree	<code>\degree</code>	°
hectare	<code>\hectare</code>	ha
hour	<code>\hour</code>	h
litre	<code>\litre</code>	L
	<code>\liter</code>	L
minute (plane angle)	<code>\arcminute</code>	'
minute (time)	<code>\minute</code>	min
second (plane angle)	<code>\arcsecond</code>	"
tonne	<code>\tonne</code>	t

Table 4: Non-SI units whose values in SI units must be obtained experimentally.

Unit	Command	Symbol
astronomical unit	<code>\astronomicalunit</code>	au
atomic mass unit	<code>\atomicmassunit</code>	u
a.u. of action	<code>\auaction</code>	$\hbar$
a.u. of charge	<code>\aucharge</code>	$e$
a.u. of energy	<code>\auenergy</code>	$E_h$
a.u. of length	<code>\aulength</code>	$a_0$
a.u. of mass	<code>\aumass</code>	$m_e$
a.u. of time	<code>\autime</code>	$\hbar E_h^{-1}$
bohr	<code>\bohr</code>	$a_0$
dalton	<code>\dalton</code>	Da
electronvolt	<code>\electronvolt</code>	eV
hartree	<code>\hartree</code>	$E_h$
n.u. of action	<code>\nuaction</code>	$\hbar$
n.u. of mass	<code>\numass</code>	$m_e$
n.u. of speed	<code>\nuspeed</code>	$c_0$
n.u. of time	<code>\nutime</code>	$m_e m_e^{-1} c_0^{-2}$

Table 5: Other non-SI units.

Unit	Command	Symbol
ångström	<code>\angstrom</code>	$\text{\AA}$
bar	<code>\bar</code>	bar
barn	<code>\barn</code>	b
bel	<code>\bel</code>	B
decibel	<code>\decibel</code>	dB
knot	<code>\knot</code>	kn
millimetre of mercury	<code>\millimetremercury</code>	mmHg
nautical mile	<code>\nauticalmile</code>	M
neper	<code>\neper</code>	Np

Table 6: Non-SI units associated with the CGS.

Unit	Command	Symbol
dyne	<code>\dyne</code>	dyn
erg	<code>\erg</code>	erg
gal	<code>\gal</code>	Gal
gauss	<code>\gauss</code>	G
maxwell	<code>\maxwell</code>	Mx
oersted	<code>\oersted</code>	Oe
phot	<code>\phot</code>	ph
poise	<code>\poise</code>	P
stilb	<code>\stilb</code>	sb
stokes	<code>\stokes</code>	St

Table 7: SI prefixes.

Prefix	Command	Symbol	Power	Prefix	Command	Symbol	Power
yocto	\yocto	y	-24	deca	\deca	da	1
zepto	\zepto	z	-21	hecto	\hecto	h	2
atto	\atto	a	-18	kilo	\kilo	k	3
femto	\femto	f	-15	mega	\mega	M	6
pico	\pico	p	-12	giga	\giga	G	9
nano	\nano	n	-9	tera	\tera	T	12
micro	\micro	μ	-6	peta	\peta	P	15
milli	\milli	m	-3	exa	\exa	E	18
centi	\centi	c	-2	zetta	\zetta	Z	21
deci	\deci	d	-1	yotta	\yotta	Y	24

SI prefixes (Table 7) [4]. The spelling “\deka” is provided for US users as an alternative to \deca.

\square, \squared, \cubic, \cubed A small number of pre-defined powers are provided as macros. \square and \cubic are intended for use before units, with \squared and \cubed going after the unit.

\cubic	$Bq^2$	\unit{\square\becquerel} \\
\cubed	$J^2 \text{lm}^{-1}$	\unit{\joule\squared\per\lumen} \\
	$lx^3 V T^3$	\unit{\cubic\lux\volt\tesla\cubed}

\tothe, \raiseto Generic powers can be inserted on a one-off basis using the \tothe and \raiseto macros. These are the only macros for units which take an argument:

$H^5$	\unit{\henry\tothe{5}} \\
$rad^{4.5}$	\unit{\raiseto{4.5}\radian}

\per Reciprocal powers are indicated using the \per macro. This applies to the next unit only, unless the sticky-per option is turned on.

$J \text{mol}^{-1} K^{-1}$	\unit{\joule\per\mole\per\kelvin} \\
$J \text{mol}^{-1} K$	\unit{\joule\per\mole\kelvin} \\
$H^{-5}$	\unit{\per\henry\tothe{5}} \\
$Bq^{-2}$	\unit{\per\square\becquerel}

\of As for generic powers, generic qualifiers are also available using the \of function:

```
\unit{\kilogram\of{metal}} \\
\qty[qualifier-mode = bracket]
{0.1}{\milli\mole\of{cat}\per\kilogram\of{prod}}
kgmetal
0.1 mmol(cat) kg(prod)-1
```

## 2.5 Unit abbreviations

In addition to the “full” names, siunitx loads a set of abbreviated versions of the SI units (Table 2.5). The standard siunitx settings only create these abbreviations within the scope of the \unit and \qty functions, meaning that no clashes should occur (for example with the standard \pm symbol).

Unit	Abbreviation	Symbol
femtogram	\fg	fg
picogram	\pg	pg
nanogram	\ng	ng
microgram	\ug	$\mu\text{g}$
milligram	\mg	mg
gram	\g	g
kilogram	\kg	kg
atomic mass unit	\amu	u
picometre	\pm	pm
nanometre	\nm	nm
micrometre	\um	$\mu\text{m}$
millimetre	\mm	mm
centimetre	\cm	cm
decimetre	\dm	dm
metre	\m	m
kilometre	\km	km
attosecond	\as	as
femtosecond	\fs	fs
picosecond	\ps	ps
nanosecond	\ns	ns
microsecond	\us	$\mu\text{s}$
millisecond	\ms	ms
second	\s	s
femtomole	\fmol	fmol
picomole	\pmol	pmol
nanomole	\nmol	nmol
micromole	\umol	$\mu\text{mol}$
millimole	\mmol	mmol
mole	\mol	mol
kilomole	\kmol	kmol
picoampere	\pA	pA
nanoampere	\nA	nA
microampere	\uA	$\mu\text{A}$

*Continued on next page*

*Continued from previous page*

Unit	Abbreviation	Symbol
milliampere	\mA	mA
ampere	\A	A
kiloampere	\kA	kA
microlitre	\uL	\mu L
millilitre	\mL	mL
litre	\L	L
hectolitre	\hL	hL
microliter	\uL	\mu L
milliliter	\mL	mL
liter	\L	L
hectoliter	\hL	hL
millihertz	\mHz	mHz
hertz	\Hz	Hz
kilohertz	\kHz	kHz
megahertz	\MHz	MHz
gigahertz	\GHz	GHz
terahertz	\THz	THz
millinewton	\mN	mN
newton	\N	N
kilonewton	\kN	kN
meganewton	\MN	MN
pascal	\Pa	Pa
kilopascal	\kPa	kPa
megapascal	\MPa	MPa
gigapascal	\GPa	GPa
milliohm	\mohm	m\Omega
kilohm	\kohm	k\Omega
megohm	\Mohm	M\Omega
picovolt	\pV	pV
nanovolt	\nV	nV
microvolt	\uV	\mu V
millivolt	\mV	mV
volt	\V	V
kilovolt	\kV	kV
watt	\W	W
microwatt	\uW	\mu W

*Continued on next page*

*Continued from previous page*

Unit	Abbreviation	Symbol
milliwatt	\mW	mW
kilowatt	\kW	kW
megawatt	\MW	MW
gigawatt	\GW	GW
joule	\J	J
microjoule	\uJ	$\mu$ J
millijoule	\mJ	mJ
kilojoule	\kJ	kJ
electronvolt	\eV	eV
millielectronvolt	\meV	meV
kiloelectronvolt	\keV	keV
megaelectronvolt	\MeV	MeV
gigaelectronvolt	\GeV	GeV
teraelectronvolt	\TeV	TeV
kilowatt hour	\kWh	kW h
farad	\F	F
femtofarad	\fF	fF
picofarad	\pF	pF
kelvin	\K	K
decibel	\dB	dB

## 2.6 Tabular material

Aligning numbers in tabular content is handled by a new column type, the **S** column. This new column type can align material using a number of different strategies, with the aim of flexibility of output without needing to alter the input. The method used as standard is to place the decimal marker in the number at the centre of the cell and to align the material appropriately (Table 8).

```
\begin{table}
  \caption{Standard behaviour of the \texttt{S} column type.}
  \label{tab:S:standard}
  \begin{tabular}{S}
    \toprule
    {Some Values} \\
    \midrule
    2.3456 \\
    34.2345 \\
    -6.7835 \\
    90.473 \\
    5642.5 \\
    1.2e3 \\
    e4 \\
    \bottomrule
  \end{tabular}
\end{table}
```

The **S** column will attempt to automatically detect material which should be placed before or after a number, and will maintain the alignment of the numerical data (Table 9).

Table 8: Standard behaviour of the S column type.

Some Values
2.345 6
34.234 5
-6.783 5
90.473
5 642.5
$1.2 \times 10^3$
$10^4$

Table 9: Detection of surrounding material in an **S** column.

## Some Values

---

If the material could be mistaken for part of a number, it should be protected by braces. The use of `\color` in a table cell will also be detected and will override any general colour applied by `siunitx`.

```
\begin{table}
  \caption{Detection of surrounding material in an \texttt{S} column.}
  \label{tab:S:extras}
  \begin{tabular}{S[color = orange]}
    \toprule
    {Some Values} \\
    12.34 \\
    \color{purple} 975,31 \\
    44.268 \textsuperscript{\emph{a}} \\
    \bottomrule
  \end{tabular}
\end{table}

\tablenum
\tablenum[<options>]{<number>}
```

Within more complex tables, aligned numbers may be desirable within the argument of `\multicolumn` or `\multirow`.<sup>1</sup> The `\tablenum` function is available to achieve alignment in these situations: this is, in effect, a macro version of the `S` column (Table 10).

```
\begin{table}
  \caption{Controlling complex alignment with the \cs{tablenum} macro.}
  \label{tab:tablenum}
  \begin{tabular}{@{}l r @{}}
    \end{table}
```

<sup>1</sup>Provided by the `multirow` package

Table 10: Controlling complex alignment with the `\tablenum` macro.

Heading	Heading	Heading	Heading
Info	More info	88.999	aaa
Info	More info		bbb
	12.34		ccc
	333.556 7	33.435	ddd
	4 563.21		

```

\toprule
Heading & Heading \\
\midrule
Info & More info \\
Info & More info \\
\multicolumn{2}{c}{\tablenum[table-format = 4.4]{12,34}} \\
\multicolumn{2}{c}{\tablenum[table-format = 4.4]{333.5567}} \\
\multicolumn{2}{c}{\tablenum[table-format = 4.4]{4563.21}} \\
\bottomrule
\end{tabular}
\hfil
\begin{tabular}{@{}l r@{}}
\toprule
Heading & Heading \\
\midrule
\multirow{2}{*}{\tablenum{88,999}} & aaa \\
& bbb \\
\multirow{2}{*}{\tablenum{33,435}} & ccc \\
& ddd \\
\bottomrule
\end{tabular}
\end{table}

```

### 3 Package control options

#### 3.1 The key–value control system

The package uses a range of different key types:

**Choice** Takes a limited number of choices, which are described separately for each key.

**Integer** Requires a number as the argument.

**Length** Requires a length, either as a literal value such as `2.0cm`, or stored as a L<sup>A</sup>T<sub>E</sub>X length.

**Literal** A key which uses the value(s) given directly, either to check input or in output.

**Macro** Requires a macro, which may need a single argument.

**Math** Similar to a **literal** option, but the input is always used in math mode, irrespective of other `siunitx` settings. Thus to text-mode only input must be placed inside the argument of a `\text` macro.

Table 11: Print options.

Option name	Type	Default
<code>color</code>	Literal	<code>&lt;none&gt;</code>
<code>mode</code>	Choice	<code>math</code>
<code>number-color</code>	Literal	<code>&lt;none&gt;</code>
<code>number-mode</code>	Choice	<code>math</code>
<code>propagate-math-font</code>	Switch	<code>false</code>
<code>reset-math-version</code>	Switch	<code>true</code>
<code>reset-text-family</code>	Switch	<code>true</code>
<code>reset-text-series</code>	Switch	<code>true</code>
<code>reset-text-shape</code>	Switch	<code>true</code>
<code>text-family-to-math</code>	Switch	<code>false</code>
<code>text-weight-to-math</code>	Switch	<code>false</code>
<code>unit-color</code>	Literal	<code>&lt;none&gt;</code>
<code>unit-mode</code>	Choice	<code>math</code>

**Meta** These are options which actually apply a number of other options.

**Switch** These are on–off switches, and recognise `true` and `false`. Giving just the key name also turns the key on.

The tables of option names use these descriptions to indicate how the keys should be used.

### 3.2 Printing

The `siunitx` package can control the font used to print output independently of the surrounding material. Which aspects of the font follow those of the surroundings is influenced by a range of setting as detailed in Section 11.

`mode` The `mode` option determines whether `siunitx` uses math or text mode when printing output. The choices are `match`, `math`, `text`. The `match` setting means that printing uses the prevailing mode unchanged whereas `math` and `text` select the appropriate TeX mode. It is possible to have different fonts in math and text modes, which will highlight the difference. The font settings which apply are also different depending on the mode. As well as the overall setting, it is possible to apply mode to numbers and units separately using the `number-mode` and `unit-mode` options.

`reset-text-family`, `reset-text-series` and `reset-text-shape` When printing in text mode, the options `reset-text-family`, `reset-text-series` and `reset-text-shape` apply. When these are active, `siunitx` resets the relevant font selection axis property when printing: the standard font setting is upright mid-weight roman (`\upshape \mdseries \rmfamily`).

```

1 234
1 234
1 234
1 234
1 234
1 234
\sisetup{mode = text}
{\itshape \num{1234}}\\
{\bfseries \num{1234}}\\
{\sfamily \num{1234}}\\
\sisetup{
    reset-text-family = false ,
    reset-text-series = false ,
    reset-text-shape = false
}
{\itshape \num{1234}}\\
{\bfseries \num{1234}}\\
{\sfamily \num{1234}}\\

```

`propagate-math-font`  
`reset-math-version`

In math mode, the font used by L<sup>A</sup>T<sub>E</sub>X is “invariant”, and this is reflected in the options available. With the standard settings, in math mode printing uses the standard math font and version (weight). The option `propagate-math-font` may be used to apply the prevailing math font to the printed material. The setting `reset-math-version` controls whether the math version is reset or not. Note that math version is typically used to set “bold math” but may also be used for other effects, for example all sanserif math.

```

kg
kg
kg
kg
kg
kg
\boldmath \unit{\kilogram}\\
\sansmath $\unit{\kilogram}$$\\
$\mathsf{\unit{\kilogram}}$$\\
\sisetup{
    propagate-math-font = true ,
    reset-math-version = false
}
\boldmath \unit{\kilogram}\\
\sansmath $\unit{\kilogram}$$\\
$\mathsf{\unit{\kilogram}}$$

```

`text-family-to-math`  
`text-weight-to-math`

The options `text-family-to-math` and `text-weight-to-math` can be used to match (as far as possible) math mode output to the surrounding text. These options work by detecting the current text settings and making the appropriate choice in math mode.

```

kg
kg
kg
kg
\sfamily \unit{\kilogram}\\
\bfseries $\unit{\kilogram}$$\\
\sisetup{
    text-family-to-math = true ,
    text-weight-to-math = true
}
\sfamily \unit{\kilogram}\\
\bfseries $\unit{\kilogram}$$

```

`color`  
`number-color`  
`unit-color`

The color of printed output can be set using the `color` option. When no color is given, printing follows the surrounding text. In contrast, when a specific color is given, it is used irrespective of the surroundings. As with `mode`, the `color` setting may also be applied to numbers and units independently.

Table 12: Options for number parsing.

Option name	Type	Default
<code>evaluate-expression</code>	Switch	<code>false</code>
<code>expression</code>	Literal	<code>#1</code>
<code>input-close-uncertainty</code>	Literal	<code>)</code>
<code>input-comparators</code>	Literal	<code>&lt;=&gt;\approx\ge\geq\gg\le\leq\ll\sim</code>
<code>input-decimal-markers</code>	Literal	<code>.</code>
<code>input-digits</code>	Literal	<code>0123456789</code>
<code>input-exponent-markers</code>	Literal	<code>dDeE</code>
<code>input-ignore</code>	Literal	<code>\{none\}</code>
<code>input-open-uncertainty</code>	Literal	<code>(</code>
<code>input-signs</code>	Literal	<code>+-\pm\mp</code>
<code>input-uncertainty-signs</code>	Literal	<code>\pm</code>
<code>parse-numbers</code>	Switch	<code>true</code>

Some text	<code>\color{red} %</code>
4 kg	<code>Some text \\</code>
More text	<code>\qty[4]{\kilogram} \\</code>
4 kg	<code>More text \\</code>
Still red here!	<code>\qty[\color = blue]{4}{\kilogram} \\</code>
	<code>Still red here!</code>

### 3.3 Parsing numbers

The package uses a sophisticated parsing system to understand numbers. This allows `siunitx` to carry out a range of formatting, as described later. All of the input options take lists of literal tokens, and are summarised in Table 12.

`input-digits`  
`input-decimal-markers`  
`input-signs`  
`input-exponent-markers`

The basic parts of a number are the digits, any sign and a separator between the integer and decimal parts. These are stored in the input options `input-digits`, `input-decimal-markers` and `input-signs`, respectively. More than one input decimal marker can be used: it will be converted by the package to the appropriate output marker. Numbers which include an exponent part also require a marker for the exponent: this again is taken from the range of tokens in the `input-exponent-markers` option.

Tokens given in the `input-ignore` list are totally passed over by `siunitx`: they will be removed from the input with no further processing.

In addition to signs, `siunitx` can recognise comparators, such as `<`. The package will automatically carry out conversions for `<<`, `>>`, `<=` and `>=` to `\ll`, `\gg`, `\le` and `\ge`, respectively.

<code>&lt;10</code>	<code>\num{&lt; 10} \\</code>
<code>&gt;&gt;5 m</code>	<code>\qty[&gt;&gt; 5]{\metre} \\</code>
<code>≤0.12</code>	<code>\num{\le 0.12}</code>

`input-open-uncertainty`  
`input-close-uncertainty`  
`input-uncertainty-signs`

In some fields, it is common to give the uncertainty in a number in brackets after the main part of the number, for example “1.234(5)”. The opening and closing symbols used for this type of input are set as `input-open-uncertainty` and `input-close-uncertainty`. Alternatively, the uncertainty may be given as a separate part following a sign. Which signs are valid for this operation is determined by the

`input-uncertainty-signs` option. As with other signs, the combination `+-` will automatically be converted to `\pm` internally.

```
9.99(9)                                \num{9.99(9)}      \\
9.99(9)                                \num{9.99 +- 0.09} \\
9.99(9)                                \num{9.99 \pm 0.09} \\
123.0(45)                               \num{123 +- 4.5} \\
12.3(60)                                \num{12.3 +- 6}
```

#### parse-numbers

The `parse-numbers` option turns the entire parsing system on and off. The option is made available for two reasons. First, if all of the numbers in a document are to be reproduced “as given”, turning off the parser will represent a significant saving in processing required. Second, it allows the use of arbitrary TeX code in numbers. If the parser is turned off, the input will be printed in math mode (requiring `\text` to protect any text in the number).

```
\num[parse-numbers = false]{\sqrt{2}}      \\
\qty[parse-numbers = false]{\sqrt{3}}{\metre} \\
\sqrt{2}                                 \\
\sqrt{3} m
```

#### evaluate-expression expression

With the standard settings, numerical input is parsed “as is” with no attempt to interpret it mathematically. By enabling the `evaluate-expression` option, the input can be processed by the standard L<sup>A</sup>T<sub>E</sub>X3 FPU (see package `xfp` for more). The nature of the expression itself can be adjusted using the `expression` setting: as standard, the entire input is simply parsed with no change, but this setting may be used to add additional steps. The *input* in such an expression is represented by `#1`. Note that the FPU uses its own syntax for numbers, most notably in that a decimal marker must be `.`.

```
\sisetup{evaluate-expression}%
\qty{2 + 4 * 3}{\joule} \\
\qty[expression = 10 * (#1)]{2 + 4 * 3}{\joule} \\
14 J \\
140 J
```

## 3.4 Post-processing numbers

Before typesetting numbers, various post-processing steps can be carried out. These involve adding or removing information from the number in a systematic way; the options are summarised in Table 13.

#### exponent-mode fixed-exponent

Numbers can be converted to scientific notation by the package. This is controlled by the `exponent-mode` option, which takes choices `input`, `fixed`, `engineering` and `scientific`. The `fixed` setting will use the exponent value by the `fixed-exponent` option. When `engineering` is set, the exponent is always a power of three.

Table 13: Number post-processing options.

Option name	Type	Default
drop-exponent	Switch	false
drop-uncertainty	Switch	false
drop-zero-decimal	Switch	false
exponent-mode	Switch	input
fixed-exponent	Integer	0
minimum-integer-digits	Integer	0
minimum-decimal-digits	Integer	0
round-half	Choice	up
round-minimum	Literal	0
round-mode	Choice	none
round-pad	Switch	true
round-precision	Integer	2

```
\num{0.001} \\
\num{0.0100} \\
\num{1200} \\
\sisetup{exponent-mode = scientific}%
\num{0.001} \\
\num{0.0100} \\
\num{1200} \\
\sisetup{exponent-mode = engineering}%
\num{0.001} \\
\num{0.0100} \\
\num{1200} \\
\sisetup{
    exponent-mode = fixed,
    fixed-exponent = 2,
}%
\num{0.001} \\
\num{0.0100} \\
\num{1200}
```

When used with a **fixed-exponent** of zero, this may be used to remove scientific notation from the input

```
\num{1.23e4} \\
\num[exponent-mode = fixed, fixed-exponent = 0]{1.23e4}
1.23 \times 104
12 300
```

Exponent mode applies *after* rounding, such that the number of decimal places for rounding is those which appear in the output.

The use of an uncertainty can be suppressed entirely using the **drop-uncertainty** option: this applies *before* rounding is attempted. Similarly, exponents can be dropped using **drop-exponent** can be used to suppress the exponent part (*after* conversion to a fixed exponent).

```

0.01(2)                                \num{0.01(2)} \\
0.01                                     \num[drop-uncertainty]{0.01(2)} \\
0.01 × 103                            \num{0.01e3} \\
0.01                                     \num[drop-exponent]{0.01e3}

```

**round-mode**  
**round-precision**  
**round-pad**

The package can round numerical input to a fixed number of significant figures or decimal places. This is controlled by the **round-mode** option, which takes the choices **none**, **figures**, **places** and **uncertainty**. When rounding is turned on, the number of digits used (either decimal places or significant figures in the mantissa) is set using the **round-precision** option. Rounding numbers with uncertainties may be carried out using the **uncertainty** setting to **round-mode**. In this case the precision is used first to round the uncertainty itself (to a number of figures), before rounding the main value to follow.

```

\num{1.23456} \\
\num{14.23} \\
\num{0.12345(9)} \\
\sisetup{
    round-mode      = places,
    round-precision = 3
}%
\num{1.23456} \\
\num{14.23} \\
\num{0.12345(9)} \\
\sisetup{
    round-mode      = figures,
    round-precision = 3
}%
\num{1.23456} \\
\num{14.23} \\
\num{0.12345(9)} \\
\sisetup{
    round-mode      = uncertainty,
    round-precision = 1
}%
\num{0.12345(9)}
\num{0.12345(23)}
\num{0.12345(234)}

```

Rounding my “extend” a short number to more digits (or figures): this is controlled by the switch **round-pad**, which is **true** as standard.

```

\sisetup{round-mode = figures, round-precision = 4}%
\num{12.3} \\
\num[round-pad = false]{12.3}
12.30
12.3

```

**round-half**

In cases where the rounded part of a number is exactly half, there are two common methods for “breaking the tie”. The choice of method is determined by the option **round-half**, which recognises the choices **up** and **even**.

```
\sisetup{
    round-mode      = figures,
    round-precision = 1,
    round-half     = up
}%
\num{0.055} \\
\num{0.045} \\
\sisetup{round-half = even}%
\num{0.055} \\
\num{0.045}
```

## round-minimum

There are cases in which rounding will result in the number reaching zero. It may be desirable to show such results as below a threshold value. This can be achieved by setting `round-minimum` to the threshold value. There will be no effect when rounding to a number of significant figures as it is not possible to obtain the value zero in these cases.

```

0.01           \sisetup{round-mode = places}%
               \num{0.0055} \\
0.00           \num{0.0045} \\
0.01           \sisetup{round-minimum = 0.01}\% TODO
               \num{0.0055} \\
0.00           \num{0.0045}

```

## drop-zero-decimal

It may be desirable to convert decimals to integers when the decimal part is zero. This is set up using the **drop-zero-decimal** option, which applies after rounding but before setting minimum numbers of digits.

```
2.0                                \num{2.0} \\  
2.1                                \num{2.1} \\  
2                                  \sisetup{drop-zero-decimal}%  
2.1                                \num{2.0} \\  
2.1                                \num{2.1}
```

minimum-decimal-digits  
minimum-integer-digits

The `minimum-decimal-digits` and `minimum-integer-digits` option may be used to pad numbers to a given size. This applies independent of any rounding.

```
\num{123} \\
\num[minimum-integer-digits = 2]{123} \\
\num[minimum-integer-digits = 4]{123} \\
\num{0.123} \\
\num[minimum-decimal-digits = 2]{0.123} \\
\num[minimum-decimal-digits = 4]{0.123} \\
123
123
0 123
0.123
0.123
0.123 0
```

Table 14: Output options for numbers.

Option name	Type	Default
<code>bracket-negative</code>	Switch	<code>false</code>
<code>close-bracket</code>	Literal	)
<code>exponent-base</code>	Literal	10
<code>exponent-product</code>	Math	<code>\times</code>
<code>group-digits</code>	Choice	<code>all</code>
<code>group-minimum-digits</code>	integer	5
<code>group-separator</code>	Literal	<code>\,</code>
<code>negative-color</code>	Literal	<code>&lt;none&gt;</code>
<code>open-bracket</code>	Literal	(
<code>output-close-uncertainty</code>	Literal	)
<code>output-decimal-marker</code>	Literal	.
<code>output-open-uncertainty</code>	Literal	(
<code>separate-uncertainty</code>	Switch	<code>false</code>
<code>tight-spacing</code>	Switch	<code>false</code>
<code>uncertainty-separator</code>	Literal	<code>&lt;none&gt;</code>

### 3.5 Printing numbers

Actually printing numbers is controlled by a number of settings, which apply ideas such as differing decimal markers, digit grouping and so on. All of these options are concerned with the appearance of output, rather than the data it conveys. The options are summarised in Table 14.

`group-digits`  
`group-four-digits`  
`group-separator`

Grouping digits into blocks of three is a common method to increase the ease of reading of numbers. The `group-digits` choice controls whether this behaviour applies, and takes the values `all`, `none`, `decimal` and `integer`. Grouping can be activated separately for the integer and decimal parts of a number using the appropriately-named values.

```
\num{12345.67890} \\
\um[group-digits = none]{12345.67890} \\
\um[group-digits = decimal]{12345.67890} \\
\um[group-digits = integer]{12345.67890}
12 345.67890
12345.67890
12345.678 90
12 345.67890
```

The separator used between groups of digits is stored by the `group-separator` option. This takes literal input and may be used in math mode: for a text-mode full space use `\_L`.

12 345	<code>\num{12345} \\</code>
12, 345	<code>\um[group-separator = {,}]{12345} \\</code>
12 345	<code>\um[group-separator = \ ]{12345}</code>

`group-minimum-digits`

Grouping is not always applied to smaller numbers, and the option `group-minimum-digits` is available to specify how many digits must be present before grouping is applied. The number of digits is considered separately for the integer and decimal parts of the number: grouping does not “cross the boundary”.

```

\num{1234} \\
\num{12345} \\
\num[group-minimum-digits = 5]{1234} \\
\num[group-minimum-digits = 5]{12345} \\
\num{1234.5678} \\
\num{12345.67890} \\
\num[group-minimum-digits = 5]{1234.5678} \\
\num[group-minimum-digits = 5]{12345.67890}
1 234
12 345
1234
12 345
1 234.5678
12 345.67890
1234.5678
12 345.67890

```

#### **output-decimal-marker**

The decimal marker used in output is set using the `output-decimal-marker` option; this can differ from the input marker.

```

\num{1.23} \\
\num[output-decimal-marker = {,}]{1.23} \\
1.23
1,23

```

When exponents are present in the input, the `exponent-base` and `exponent-product` options set the obvious parts of the output.

```

\num[exponent-product = \times]{1e2} \\
\num[exponent-product = \cdot]{1e2} \\
\num[exponent-base = 2]{1e2}
102
102
22

```

#### **separate-uncertainty uncertainty-separator output-open-uncertainty output-close-uncertainty**

When input is given including an uncertainty in a number, it can be printed either with the uncertainty in brackets or as a separate number. This behaviour is controlled by the `separate-uncertainty` choice. If the uncertainty is given in brackets, a space may be added between the main number and the uncertainty: this is stored using the `uncertainty-separator` option. The opening and closing brackets used are stored in `output-open-uncertainty` and `output-close-uncertainty`, respectively.

```

\num{1.234(5)} \\
\num[separate-uncertainty = true]{1.234(5)} \\
\sisetup{
    output-open-uncertainty  = [,
    output-close-uncertainty = ],
    uncertainty-separator   = \,
}%
\num{1.234(5)}
1.234(5)
1.234 ± 0.005
1.234 [5]

```

Table 15: Angle options.

Option name	Type	Default
angle-mode	Choice	input
angle-symbol-over-decimal	Switch	false
arc-separator	Literal	<i>(empty)</i>
fill-arc-degrees	Switch	false
fill-arc-minutes	Switch	false
fill-arc-seconds	Switch	false
number-angle-product	Literal	<i>(empty)</i>

Notice that `siunitx` correctly interprets uncertainties which cross the decimal marker position whether these are separated out or not.

8.2(13)	<code>\num{8.2(13)} \\</code>
$8.2 \pm 1.3$	<code>\num[separate-uncertainty]{8.2(13)}</code>

#### `negative-color`

The package can detect negative mantissa values and alter print color accordingly. This is disabled by setting the option to an empty value.

-15 673	<code>\num{-15673} \\</code>
<b>-15 673</b>	<code>\num[negative-color = red]{-15673}</code>

#### `bracket-negative`

A common means to display negative numbers in financial situations is to place them in brackets. This can be carried out automatically using the `bracket-negative-numbers` option.

-15 673	<code>\num{-15673} \\</code>
(15 673)	<code>\num;bracket-negative]{-15673} \\</code>
-10 m	<code>\qty{-10}{\metre} \\</code>
(10) m	<code>\qty;bracket-negative]{-10}{\metre}</code>

#### `tight-spacing`

Under some circumstances it may be desirable to “squeeze” the output spacing. This is turned on using the `tight-spacing` switch, which compresses spacing where possible.

$2 \times 10^3$	<code>\num{2e3} \\</code>
$2 \times 10^3$	<code>\num[tight-spacing = true]{2e3}</code>

## 3.6 Angles

Angle processing provided by the `\ang` function has a set of options which apply in addition to the general ones set up for number processing.

#### `angle-mode`

The format in which angles are printed can be set using the `angle-mode` option. With the standard setting (`input`), the angle is printed as-given. By setting the option to `arc` or `decimal`, the output format can be set to an arc (degrees/minutes/seconds) or decimal value. Conversion uses the L<sup>A</sup>T<sub>E</sub>X3 floating-point unit, so is limited to 16 decimal places.

$2.67^\circ$ $2^\circ 3' 4''$ $2^\circ 40' 12''$ $2^\circ 3' 4''$ $2.67^\circ$ $2.051\ 111\ 111\ 111\ 111^\circ$	$\text{\ang}{2.67} \\$ $\text{\ang}{2;3;4} \\$ $\text{\ang[angle-mode = arc]}{2.67} \\$ $\text{\ang[angle-mode = arc]}{2;3;4} \\$ $\text{\ang[angle-mode = decimal]}{2.67} \\$ $\text{\ang[angle-mode = decimal]}{2;3;4} \\$
---	--

**number-angle-product**

The separator between the number and angle symbol (degrees, minutes or seconds) can be set using the **number-angle-product** option, independent of the related **number-unit-product** option used by the `\qty` command.

$2.67^\circ$ $2.67^\circ$	$\text{\ang}{2.67} \\$ $\text{\ang[number-angle-product = ,]}{2.67}$
------------------------------	--

**arc-separator**

When angles are printed in arc format, the separation of the different parts is set up using the **arc-separator** option.

$6^\circ 7' 6.5''$ $6^\circ 7' 6.5''$	$\text{\ang}{6;7;6.5} \\$ $\text{\ang[arc-separator = ,]}{6;7;6.5}$
--	---

**fill-arc-degrees**  
**fill-arc-minutes**  
**fill-arc-seconds**

Zero-filling for the degree, minute or second parts of an arc is controlled using the **fill-arc-degrees**, **fill-arc-minutes** and **fill-arc-seconds** options. All are off as standard.

```

\ang{-1;;} \\
\ang{;-2;} \\
\ang{;;-3;} \\
{
  -1^\circ
  -2'
  -3"
  -1^\circ
  -0^\circ 2'
  -0^\circ 3"
  -1^\circ 0'
  -2'
  -0' 3"
  -1^\circ 0"
  -2' 0"
  -3"
}
{
  \sisetup{fill-arc-degrees}
  \ang{-1;;} \\
  \ang{;-2;} \\
  \ang{;;-3;} \\
}
{
  \sisetup{fill-arc-minutes}
  \ang{-1;;} \\
  \ang{;-2;} \\
  \ang{;;-3;} \\
}
{
  \sisetup{fill-arc-seconds}
  \ang{-1;;} \\
  \ang{;-2;} \\
  \ang{;;-3;} \\
}

```

**angle-symbol-over-decimal**

In some subject areas, most notably astronomy, the angle symbols are given over the decimal marker, rather than at the end of the number. This behaviour is available using the **angle-symbol-over-decimal** option.

Table 16: Unit output options.

Option name	Type	Default
bracket-unit-denominator	Switch	<code>true</code>
font-command	Literal	<code>\mathrm</code>
forbid-literal-units	Switch	<code>false</code>
inter-unit-product	Literal	<code>\,</code>
parse-units	Switch	<code>true</code>
per-mode	Choice	<code>power</code>
per-symbol	Literal	<code>/</code>
qualifier-mode	Choice	<code>subscript</code>
qualifier-phrase	Literal	<code>{empty}</code>
sticky-per	Switch	<code>false</code>

### 3.7 Using units

Part of the power of `siunitx` is the ability to alter the output format for units without changing the input. The behaviour of units is therefore controlled by a number of options which alter either the processing of units or the output directly (Table 16).

`inter-unit-product`

The separator between each unit is stored using the `inter-unit-product` option. The standard setting is a thin space: another common choice is a centred dot. To get the correct spacing it is necessary to use `\ensuremath{\cdot}` in the latter case.

```
\unit{\farad\squared\lumen\candela} \\
\unit[inter-unit-product = \ensuremath{\cdot}]{\farad\squared\lumen\candela}
F2 lm cd
F2 · lm · cd
```

`per-mode`  
`per-symbol`  
`bracket-unit-denominator`

The handling of `\per` is altered using the `per-mode` choice option. The standard setting is `power`, meaning that `\per` generates reciprocal powers for units. Setting the option to `fraction` uses the `\frac` function to typeset the positive and negative powers of a unit separately.

```
\unit{\joule\per\mole\per\kelvin} \\
\unit{\metre\per\second\squared} \\
\unit[per-mode = fraction]{\joule\per\mole\per\kelvin} \\
\unit[per-mode = fraction]{\metre\per\second\squared}
J mol-1 K-1
m s-2
J
--- mol K
m
--- s2
```

The closely-related `power-positive-first` setting acts in the same way but places all of the positive powers before any negative ones.

A mol<sup>-1</sup> s  
A s mol<sup>-1</sup>

```
\unit{\ampere\per\mole\second} \\
\unit[per-mode = power-positive-first]{\ampere\per\mole\second}
```

It is possible to use a symbol (usually `/`) to separate the two parts of a unit by setting `per-mode` to `symbol`; the symbol used is stored using the setting `per-symbol`. This method for displaying units can be ambiguous, and so brackets are added unless `bracket-unit-denominator` is set to `false`. Notice that `bracket-unit-denominator` only applies when `per-mode` is set to `symbol` or `symbol-or-fraction`.

```
\sisetup{per-mode = symbol}%
\unit{\joule\per\mole\per\kelvin} \\
\unit{\metre\per\second\squared} \\
\unit[per-symbol = \text{div}]{\joule\per\mole\per\kelvin} \\
\unit[bracket-unit-denominator = false]{\joule\per\mole\per\kelvin} \\
J/(mol K) \\
m/s2 \\
J div (mol K) \\
J/mol K
```

The often-requested (but mathematically invalid) `repeated-symbol` option is also available to repeat the symbol for each `\per`.

```
\unit[per-mode = repeated-symbol]{\joule\per\mole\per\kelvin} \\
J/mol/K
```

Finally, it is possible for the behaviour of the `\per` function to depend on the prevailing math style. Setting `per-mode` to `symbol-or-fraction` will use the `symbol` setting for inline math, and the `fraction` setting when used in display math.

```
\sisetup{per-mode = symbol-or-fraction}%
$ \unit{\joule\per\mole\per\kelvin} $ \\
\[
  \unit{\joule\per\mole\per\kelvin} \\
  \unit{\joule\per\mole\per\kelvin} \\
$ \\
  \displaystyle
  \unit{\joule\per\mole\per\kelvin} \\
$ \\
\[
  \textstyle
  \unit{\joule\per\mole\per\kelvin}
\] \\
J/(mol K)
```

$$\frac{J}{\text{mol K}}$$

$$J/(mol K)$$

$$\frac{J}{\text{mol K}}$$

$$J/(mol K)$$

#### `sticky-per`

By default, `\per` applies only to the next unit given.<sup>2</sup> By setting the `sticky-per` flag, this behaviour is changed so that `\per` applies to all subsequent units.

---

<sup>2</sup>This is the standard method of reading units in English: for example,  $J\text{mol}^{-1}\text{K}^{-1}$  is pronounced “joules per mole per kelvin”.

```
\unit{\pascal\per\gray\henry} \\
\unit[sticky-per]{\pascal\per\gray\henry}
Pa Gy-1 H
Pa Gy-1 H-1
```

**qualifier-mode  
qualifier-phrase**

Unit qualifiers can be printed in three different formats, set by the `qualifier-mode` option. The standard setting is `subscript`, while the options `bracket`, `combine` and `phrase` are also possible. With the last settings, powers can lead to ambiguity and are automatically detected and brackets added as appropriate.

```
\unit{kilogram\of{pol}\squared\per\mole\of{cat}\per\hour} \\
\unit[qualifier-mode = bracket]
  {\kilogram\of{pol}\squared\per\mole\of{cat}\per\hour} \\
\unit[qualifier-mode = combine]
  {\deci\bel\of{i}}
kg2pol mol-1cat h-1
kg(pol)2 mol(cat)-1 h-1
dBi
```

The `phrase` option is used with `qualifier-phrase`, which allows for example a space or other linking text to be inserted.

```
\sisetup{qualifier-mode = phrase, qualifier-phrase = \ }%
\unit{kilogram\of{pol}\squared\per\mole\of{cat}\per\hour} \\
\sisetup{qualifier-phrase = \ \mbox{of}\ }%
\unit{kilogram\of{pol}\squared\per\mole\of{cat}\per\hour}
kg pol2 mol cat-1 h-1
kg of pol2 mol of cat-1 h-1
```

**parse-units**

Normally, `siunitx` is used with the unit parse enabled, and only prints units directly if there is literal input. However, if the input is known to be essentially consistent and high performance is desired, then the parser can be turned off using the `parse-units` switch.

300 MHz	<code>\qty{300}{\MHz}</code>
300 MHz	<code>\qty[parse-units = false]{300}{\MHz}</code>

**forbid-literal-units**

Some users may prefer to completely disable the use of literal input in units, for example to enforce consistency. This can be accomplished by setting the `forbid-literal-units` switch. With this option enabled, only macro-based units can be used in a document. This only applies when `parse-units` is `true`.

**font-command**

The command used to set unit themselves may be adjusted using the `font-command` option. This is typically set to `\mathrm`.

lm	<code>\unit{\lumen}</code>
lm	<code>\unit[font-command = \mathit]{\lumen}</code>

Table 17: Options for tabular material.

Option name	Type	Default
<code>table-align-comparator</code>	Switch	<code>true</code>
<code>table-align-exponent</code>	Switch	<code>true</code>
<code>table-align-text-after</code>	Switch	<code>true</code>
<code>table-align-text-before</code>	Switch	<code>true</code>
<code>table-align-uncertainty</code>	Switch	<code>true</code>
<code>table-alignment</code>	Meta	<code>center</code>
<code>table-alignment-mode</code>	Choice	<code>marker</code>
<code>table-auto-round</code>	Switch	<code>false</code>
<code>table-column-width</code>	Length	<code>Opt</code>
<code>table-fixed-width</code>	Switch	<code>false</code>
<code>table-format</code>	Special	<code>2.2</code>
<code>table-number-alignment</code>	Choice	<code>center</code>
<code>table-text-alignment</code>	Choice	<code>center</code>

### 3.8 Tabular material

Processing of material in tables obeys the same settings as described for the functions already described. However, there are some settings which apply only to the layout of tabular material (Table 17).

#### `table-mode`

The method used by `siunitx` to align numbers is selected using the `table-mode` option, which may be one of `marker`, `format` or `<none>`. With the standard setting, `<marker>`, the package centers the decimal marker in a tabular column, potentially leaving white space at the shorter end of a number. The `<format>` mode uses information from the `<table-format>` key to construct a model: this is then used to define the space available to a number. For asymmetrical numbers, this method is strongly preferable. Finally, `none` disables alignment entirely: numbers are simply parsed.

#### `table-number-alignment`

When `table-mode` is set to `<format>` or `<none>`, the placement of the number “block” within the cell as a whole is set by the `<table-number-alignment>` option, which may be one of `<left>`, `<center>` or `<right>`. (When `table-mode` is set to `<marker>`, the decimal marker is always centered in the cell.) The different alignment choices are illustrated in Table 18, which uses somewhat exaggerated column headings to show the relative position of the cell contents.

```
\begin{table}
  \caption{Aligning the \texttt{S} column.}
  \label{tab:S:align}
  \centering
  \sisetup{table-format = 2.4, table-alignment-mode = format}
  \begin{tabular}{@{}c@{}}
    S[table-alignment-mode = marker]
    S[table-number-alignment = center]
    S[table-number-alignment = left]
    S[table-number-alignment = right]
  @{}}
  \toprule
  {Some Values} & {Some Values} & {Some Values} & {Some Values} \\
  \midrule
```

Table 18: Aligning the `S` column.

Some Values	Some Values	Some Values	Some Values
2.345 6	2.345 6	2.345 6	2.345 6
34.234 5	34.234 5	34.234 5	34.234 5
56.783 5	56.783 5	56.783 5	56.783 5
90.473	90.473	90.473	90.473

Table 19: Parsing without aligning in an `S` column.

Decimal-centred	Simple centring
12.345	12.345
6.78	6.78
-88.8(9)	-88.8(9)
$4.5 \times 10^3$	$4.5 \times 10^3$

```

2.3456 & 2.3456 & 2.3456 & 2.3456 \\
34.2345 & 34.2345 & 34.2345 & 34.2345 \\
56.7835 & 56.7835 & 56.7835 & 56.7835 \\
90.473 & 90.473 & 90.473 & 90.473 \\
\bottomrule
\end{tabular}
\end{table}

```

When the alignment mode is set to `none`, numbers are simply collected and parsed without any further processing, as illustrated in Table 19.

```

\begin{table}
\caption{Parsing without aligning in an \texttt{\{S\}} column.}
\label{tab:S:parse}
\begin{tabular}
{@{}}
S
S[table-alignment-mode = none]
@{}}
\toprule
{Decimal-centred} &
{Simple centring} \\
\midrule
12.345 & 12.345 \\
6,78 & 6,78 \\
-88.8(9) & -88.8(9) \\
4.5e3 & 4.5e3 \\
\bottomrule
\end{tabular}
\end{table}

```

`table-format`

When the `table-alignment-mode` is set to `format`, `siunitx` uses the information set in  $\langle\text{table-format}\rangle$  to construct a “model” which defines the space to reserve for a number. The `table-format` key is interpreted in much the same way as a table cell. The numerical part should consist of a number showing how many figures to reserve in each part of the

Table 20: Reserving space in `S` columns.

Values	Values	Values	Values	Values	Values
2.3	2.3	2.3(5)	2.3 ± 0.5	2.3	$2.3 \times 10^8$
34.23	34.23	34.23(4)	34.23 ± 0.04	34.23	34.23
56.78	56.78	56.78(3)	56.78 ± 0.03	-56.78	$56.78 \times 10^3$
3.76	3.76	3.76(2)	3.76 ± 0.02	±3.76	$10^6$

input, plus any comparators, signs, *etc.* A variety of examples are given in Table 20.

```
\begin{table}
  \caption{Reserving space in \texttt{S} columns.}
  \label{tab:S:format}
  \sisetup{
    table-alignment-mode = format,
    table-number-alignment = center,
  }
  \begin{tabular}{@{}}
    S[table-format = 2.2]
    S[table-format = 2.2, table-number-alignment = right]
    S[table-format = 2.2(1)]
    S[table-format = 2.2(1), separate-uncertainty]
    S[table-format = +2.2]
    S[table-format = 2.2e1]
  @{}}
  \toprule
    {Values}
    & {Values}
    & {Values}
    & {Values}
    & {Values}
    & {Values} \\
  \midrule
    2.3 & 2.3 & 2.3(5) & 2.3(5) & 2.3 & 2.3e8 \\
    34.23 & 34.23 & 34.23(4) & 34.23(4) & 34.23 & 34.23 \\
    56.78 & 56.78 & 56.78(3) & 56.78(3) & -56.78 & 56.78e3 \\
    3.76 & 3.76 & 3.76(2) & 3.76(2) & +3.76 & e6 \\
  \bottomrule
  \end{tabular}
\end{table}
```

It is important to note that any parts of a number *not* specified in the table format argument are set to be absent (the number of figures is set to zero). Setting the `table-format` option also resets `table-alignment-mode` to `format`.

Space for material before and after the `S` column can be reserved by giving model text as part of the `table-format` key. This is then used to provide the necessary gap while maintaining alignment (Table 21).

```
\begin{table}
  \caption{Text before and after numbers.}
  \label{tab:S:ends}
  \sisetup{table-format = {now }2.4{\textsuperscript{\emph{a}}}}
  \begin{tabular}{@{}S@{}}

```

Table 21: Text before and after numbers.

Values
2.345 6
34.234 5 <sup>a</sup>
56.783 5
now 90.473

Table 22: The `table-align-exponent` option

Header	Header
$1.2 \times 10^3$	$1.2 \times 10^3$
$1.234 \times 10^{56}$	$1.234 \times 10^{56}$

```
\toprule
{Values} \\
\midrule
2.3456 \\
34.2345 \textsuperscript{\emph{a}} \\
56.7835 \\
now~ 90.473 \\
\bottomrule
\end{tabular}
\end{table}
```

#### table-align-exponent table-align-uncertainty

When printing exponents in tables, there is a choice of aligning the exponent parts or having these close up to the mantissa. This is controlled by the `table-align-exponent` option (Table 22). Similarly, uncertainty parts which are printed separately from the mantissa can be aligned or closed up. This is set by the `table-align-uncertainty` option (Table 23). Finally, the same approach is available for the comparator with the `table-align-comparator` option (Table 24).

```
\begin{table}
\caption{The \opt{table-align-exponent} option}
\label{tab:align:exp}
\sisetup{table-format = 1.3e2}
\begin{tabular}{@{}SS[table-align-exponent = false]@{}}
\toprule
{Header} & {Header} \\
\midrule
1.2e3 & 1.2e3 \\
1.234e56 & 1.234e56 \\
\bottomrule
\end{tabular}
\end{table}

\begin{table}
\caption{The \opt{table-align-uncertainty} option}
\label{tab:align:uncert}
\sisetup{
separate-uncertainty,
```

Table 23: The `table-align-uncertainty` option

Header	Header
$1.2 \pm 0.1$	$1.2 \pm 0.3$
$1.234 \pm 0.005$	$1.234 \pm 0.005$

Table 24: The `table-align-comparator` option

Header	Header
$> 1.2$	$> 1.2$
$< 12.34$	$< 12.34$

```

    table-format = 1.3(1),
}
\begin{tabular}{@{}SS[table-align-uncertainty = false]@{}}
  \toprule
  {Header} & {Header} \\
  \midrule
  1.2(1) & 1.2(3) \\
  1.234(5) & 1.234(5) \\
  \bottomrule
\end{tabular}
\end{table}

\begin{table}
\caption{The \opt{table-align-comparator} option}
\label{tab:align:comp}
\sisetup{table-format = >2.2}
\begin{tabular}{@{}SS[table-align-comparator = false]@{}}
  \toprule
  {Header} & {Header} \\
  \midrule
  > 1.2 & > 1.2 \\
  < 12.34 & < 12.34 \\
  \bottomrule
\end{tabular}
\end{table}

```

`table-align-text-before`  
`table-align-text-after`

Note markers are often given in tables after the numerical content. It may be desirable for these to close up to the numbers. Whether this takes place is controlled by the `table-align-text-before` and ...-`after` option (Table 25).

```

\begin{table}
\caption{Closing notes up to text.}
\label{tab:S:notes}
\newrobustcmd{\NoteMark[1]{%
  \textsuperscript{\emph{#1}}%
}}
\sisetup{table-format = {\NoteMark{a}}2.4}
\begin{tabular}{@{}S}
  S
\end{tabular}
\end{table}

```

Table 25: Closing notes up to text.

Values	Values	Values	Values
2.345 6	2.345 6	2.345 6	2.345 6
<sup>a</sup> 4.234	<sup>a</sup> 4.234	34.234	<sup>a</sup> 34.234 <sup>a</sup>
<sup>b</sup> 0.78	<sup>b</sup> 0.78	56.78	<sup>b</sup> 56.78 <sup>b</sup>
<sup>d</sup> 88	<sup>d</sup> 88	90.4	<sup>c</sup> 90.4 <sup>c</sup>
		88	<sup>d</sup> 88 <sup>d</sup>

```

S[table-align-text-before = false]
@{}}
\toprule
{Values} & {Values} \\
\midrule
2.3456 & 2.3456 \\
\NoteMark{a} 4.234 & \NoteMark{a} 4.234 \\
\NoteMark{b} .78 & \NoteMark{b} .78 \\
\NoteMark{d} 88 & \NoteMark{d} 88 \\
\bottomrule
\end{tabular}
\hfil
\sisetup{table-format = 2.4\NoteMark{a}}
\begin{tabular}{l}
S
S[table-align-text-after = false]
}
\toprule
{Values} & {Values} \\
\midrule
2.3456 & 2.3456 \\
34.234 \NoteMark{a} & 34.234 \NoteMark{a} \\
56.78 \NoteMark{b} & 56.78 \NoteMark{b} \\
90.4 \NoteMark{c} & 90.4 \NoteMark{c} \\
88 \NoteMark{d} & 88 \NoteMark{d} \\
\bottomrule
\end{tabular}
\end{table}

```

#### table-auto-round

The contents of table cells can automatically be rounded or zero-filled to the number of decimal digits given for the decimal part of the `table-format` option. This mode is activated using the `table-auto-round` switch, as illustrated in Table 26.

```

\begin{table}
\centering
\caption{The \opt{table-auto-round} option.}
\label{tab:S:auto}
\sisetup{table-format = 1.3}
\begin{tabular}{@{}SS[table-auto-round]@{}}
\toprule
{Header} & {Header} \\
\midrule
1.2 & 1.2 \\
1.2345 & 1.2345 \\
\bottomrule
\end{tabular}

```

Table 26: The `table-auto-round` option.

Header	Header
1.2	1.200
1.2345	1.235

```
\bottomrule
\end{tabular}
\end{table}
```

#### parse-numbers

When the `parse-numbers` option is set to `false`, then the alignment code for tables takes a different approach. The output is always set in math mode, and alignment takes place at the first decimal marker. This is achieved by making it active in math mode. When reserving space for content only the integer and decimal values for the mantissa are considered (Table 27).

```
\begin{table}
  \caption{Aligning without parsing.}
  \label{tab:S:noparsed}
  \sisetup{
    parse-numbers = false,
    table-format = 3.3
  }
  \centering
  \begin{tabular}{@{}c@{}}
    S
    S[table-number-alignment = center]
    S[table-number-alignment = right]
    S[table-number-alignment = left]
    @{}
  \end{tabular}
  \toprule
    {Some values}
    & {Some values}
    & {Some values}
    & {Some values} \\
  \midrule
    2.35 & 2.35 & 2.35 & 2.35 \\
    34.234 & 34.234 & 34.234 & 34.234 \\
    56.783 & 56.783 & 56.783 & 56.783 \\
    3,762 & 3,762 & 3,762 & 3,762 \\
    \sqrt{2} & \sqrt{2} & \sqrt{2} & \sqrt{2} \\
  \bottomrule
  \end{tabular}
\end{table}
```

#### drop-exponent

In cases where data cover a range of values, printing using a fixed exponent in a table may make presentation clearer. In these cases, dropping the exponent value from the table is useful. The general numerical options `drop-exponent` combined with `exponent-mode = fixed` can be used to achieve this (Table 28).

```
\begin{table}
  \caption{The \opt{table-omit-exponent} option}
  \label{tab:exp:omit}
  \begin{array}{l}
    \dots
  \end{array}
\end{table}
```

Table 27: Aligning without parsing.

Some values	Some values	Some values	Some values
2.35	2.35	2.35	2.35
34.234	34.234	34.234	34.234
56.783	56.783	56.783	56.783
3.762	3.762	3.762	3.762
$\sqrt{2}$	$\sqrt{2}$	$\sqrt{2}$	$\sqrt{2}$

Table 28: The `table-omit-exponent` option

Header	Header / $10^3$
$1.2 \times 10^3$	1.2
$3 \times 10^2$	0.3
$1.0 \times 10^4$	10

```

\begin{tabular}{@{}}
  S[table-format = 1.1e1]
  S[
    drop-exponent = true,
    exponent-mode = fixed,
    fixed-exponent = 3,
    table-format = 2.1,
  ]
  @{}
  \toprule
  {Header} & \multicolumn{1}{c}{Header / \num{e3}} \\
  \midrule
  1.2e3 & 1.2e3 \\
  3e2 & 3e2 \\
  1.0e4 & 1.0e4 \\
  \bottomrule
\end{tabular}
\end{table}

```

`table-column-width`  
`table-fixed-width`

Usually, the width of the numerical column is allowed to vary depending on the content. However, there are cases where a strictly fixed width is desirable. For these cases, the `table-fixed-width` and `table-column-width` options are available. The `table-fixed-width` option activates fixed-width columns, whilst `table-column-width` defines the target width (Table 29).

```

\begin{table}
  \caption{Fixed-width columns.}
  \label{tab:width:fixed}
  \begin{tabular}{@{}}
    S
    S[table-column-width = 2cm]
  @{}
  \toprule
  {Flexible} &

```

Table 29: Fixed-width columns.

Flexible	Fixed
1.23	1.23
45.6	45.6

Table 30: Right-aligning under a heading.

Long header
12.33
2
1 234

```
{Fixed}    \\
\midrule
1.23 & 1.23 \\
45.6 & 45.6 \\
\bottomrule
\end{tabular}
\end{table}
```

The `table-column-width` option can also be used to achieve special effects. One example is centring a column of numbers under a wide heading, with the numbers themselves right-aligned (Table 30).

```
\begin{table}
\centering
\caption{Right-aligning under a heading.}
\label{tab:width:special}
\settowidth{\mylength}{Long header}
\sisetup{
  table-alignment-mode = none ,
  table-column-width   = \mylength ,
  table-number-alignment = right
}
\begin{tabular}{@{}S@{}}
\toprule
{Long header} \\
\midrule
12.33 \\
2 \\
1234 \\
\bottomrule
\end{tabular}
\end{table}
```

`table-text-alignment`  
`table-alignment`

Cell contents which are not part of a number can be protected using braces, as illustrated. Cells which contain no numerical data at all are aligned using the setting specified by the `table-text-alignment` option, which recognises the values `center`, `left` and `right` (Table 31).

```
\begin{table}
```

Table 31: Aligning text in S columns.

Values	Values	Values
992.435	992.435	992.435
7 734.234 4	7 734.234 4	7 734.234 4
56.783 4	56.783 4	56.783 4
3.746 2	3.746 2	3.746 2

```
\caption{Aligning text in \texttt{S} columns.}
\label{tab:S:text}
\sisetup{table-format = 4.4}
\centering
\begin{tabular}{@{}c
S
S[table-text-alignment = left]
S[table-text-alignment = right]
@{}}
\toprule
{Values}
& {Values}
& {Values} \\
\midrule
992.435 & 992.435 & 992.435 \\
7734.2344 & 7734.2344 & 7734.2344 \\
56.7834 & 56.7834 & 56.7834 \\
3,7462 & 3,7462 & 3,7462 \\
\bottomrule
\end{tabular}
\end{table}
```

#### table-alignment

The table alignment options `table-number-alignment` and `table-text-alignment` can be set to the same value using the `table-alignment` option. This will set all three alignment options to the same value (one of `center`, `right` or `left`).

## 4 Installation

For most users, there will be no need to explicitly install `siunitx`: it is available from the package management system in current TeX Live and MiKTeX systems.

For manual installation, the package is available from CTAN. As well as the raw source files, CTAN hold the package as a pre-extracted zip file, `siunitx.tds.zip`. The latter is most convenient for most users: simply unzip this in your local `texmf` directory.

The package requires L<sup>A</sup>T<sub>E</sub>X3 support as provided in the l3kernel and l3packages bundles. Both of these are included in TeX Live and MiKTeX, or are again available in ready-to-install form from CTAN.

## 5 Thanks

Many users have provided feedback, bug reports and ideas for new features for `siunitx`: thanks to all of them. Particular thanks to Stefan Pinnow, who has taken the lead role as

beta tester for `siunitx`, finding incorrect output, bad documentation and the odd spelling mistake in the documentation. Thanks also to Enrico Gregorio for encouraging me to complete a fully `expl3`-compliant version of the package. Thanks also to Danie Els and Marcel Heldoorn for the `SIstyle` and `Slunits` packages, respectively, which provided the starting point for the development of `siunitx`.

## 6 Making suggestions and reporting bugs

Feedback on `siunitx` is always welcome, either to make suggestions or to report problems. When sending feedback, it is always useful if a small example file is included, showing the bug being reported or illustrating the desired output. It is helpful if a “reference rendering” is included, showing what the output should look like. A typical example file might read

```
\listfiles
% Use the article class unless the problem is class-dependent
\documentclass{article}
\usepackage{siunitx}
% Other packages loaded as required
\begin{document}
Reference output: $1.23\,\mathrm{m}$

siunitx output: \qty{1.23}{\metre}
\end{document}
```

As illustrated, it is usually best to use the `article` class and to only load packages which are needed to show the issue. It is also useful to include a copy of the log file generate by L<sup>A</sup>T<sub>E</sub>X when reporting a bug (as the versions of packages can be important to solving the issue).

Feedback can be sent in a range of ways. The development code and issue tracker are hosted on GitHub. Issues opened there are visible to other users and makes sure that they cannot be forgotten.

## References

- [1] *The International System of Units (SI)*, <https://www.bipm.org/en/measurement-units/>.
- [2] *SI base units*, <https://www.bipm.org/en/publications/si-brochure/section2-1.html>.
- [3] *Units with special names and symbols; units that incorporate special names and symbols*, <https://www.bipm.org/en/publications/si-brochure/section2-2-2.html>.
- [4] *SI Prefixes*, <https://www.bipm.org/en/publications/si-brochure/chapter3.html>.
- [5] *Formatting the value of a quantity*, <https://www.bipm.org/en/publications/si-brochure/section5-3-3.html>.

- [6] *Stating values of dimensionless quantities, or quantities of dimension one*, <https://www.bipm.org/en/publications/si-brochure/section5-3-7.html>.
  - [7] *Non-SI units accepted for use with the International System of Units*, <https://www.bipm.org/en/publications/si-brochure/table6.html>.
  - [8] *Non-SI units whose values in SI units must be obtained experimentally*, <https://www.bipm.org/en/publications/si-brochure/table7.html>.
  - [9] *Other non-SI units*, <https://www.bipm.org/en/publications/si-brochure/table8.html>.
  - [10] *Non-SI units associated with the CGS and the CGS-Gaussian system of units*, <https://www.bipm.org/en/publications/si-brochure/table9.html>.

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

drop-zero-decimal (option) . . . . .	19	\hour . . . . .	5
\dyne . . . . .	6	\Hz . . . . .	9
<b>E</b>			
\electronvolt . . . . .	6	input-close-uncertainty (option) . . . . .	15
\erg . . . . .	6	input-comparators (option) . . . . .	15
\eV . . . . .	10	input-decimal-markers (option) . . . . .	15
evaluate-expression (option) . . . . .	16	input-digits (option) . . . . .	15
\exa . . . . .	7	input-exponent-markers (option) . . . . .	15
exponent-base (option) . . . . .	21	input-ignore (option) . . . . .	15
exponent-mode (option) . . . . .	16	input-open-uncertainty (option) . . . . .	15
exponent-product (option) . . . . .	21	input-signs (option) . . . . .	15
expression (option) . . . . .	16	input-uncertainty-signs (option) . . . . .	15
inter-unit-product (option) . . . . .			
24			
<b>F</b>			
\F . . . . .	10	<b>J</b>	
\farad . . . . .	5	\J . . . . .	10
\femto . . . . .	7	\joule . . . . .	5
\fF . . . . .	10	<b>K</b>	
\fg . . . . .	8	\K . . . . .	10
fill-arc-degrees (option) . . . . .	23	\kA . . . . .	9
fill-arc-minutes (option) . . . . .	23	\katal . . . . .	5
fill-arc-seconds (option) . . . . .	23	\kelvin . . . . .	5
fixed-exponent (option) . . . . .	16	\keV . . . . .	10
\fmol . . . . .	8	\kg . . . . .	8
font-command (option) . . . . .	26	\kHz . . . . .	9
forbid-literal-units (option) . . . . .	26	\kilo . . . . .	7
\fs . . . . .	8	\kilogram . . . . .	5
<b>G</b>			
\g . . . . .	8	\kJ . . . . .	10
\gal . . . . .	6	\km . . . . .	8
\gauss . . . . .	6	\kmol . . . . .	8
\ge . . . . .	15	\kN . . . . .	9
\geq . . . . .	15	\knot . . . . .	6
\GeV . . . . .	10	\kohm . . . . .	9
\gg . . . . .	15	\kPa . . . . .	9
\GHz . . . . .	9	\kV . . . . .	9
\giga . . . . .	7	\kW . . . . .	10
\GPa . . . . .	9	\kWh . . . . .	10
\gray . . . . .	5	<b>L</b>	
group-digits (option) . . . . .	20	\L . . . . .	9
group-four-digits (option) . . . . .	20	\l . . . . .	9
group-minimum-digits (option) . . . . .	20	\le . . . . .	15
group-separator (option) . . . . .	20	\leq . . . . .	15
\GW . . . . .	10	\liter . . . . .	5
<b>H</b>			
\hartree . . . . .	6	\litre . . . . .	5
\hectare . . . . .	5	\ll . . . . .	15
\hecto . . . . .	7	<b>M</b>	
\henry . . . . .	5	\lumen . . . . .	5
\hertz . . . . .	5	\lux . . . . .	5
\hL . . . . .	9	\m . . . . .	8
\hl . . . . .	9	\mA . . . . .	9
\mathrm . . . . .			
24			

\maxwell	6	number-color (option)	14
\mega	7	number-mode (option)	13
\meter	4	\nuspeed	6
\meter	4	\nutime	6
\metre	4, 5	\nV	9
\MeV	10		
\meV	10		
\mg	8	\oersted	6
\MHz	9	\of	7
\mHz	9	\of	7
\micro	7	\ohm	5
\milli	7	options:	
\millimetremercury	6	angle-mode	22
minimum-decimal-digits (option)	19	angle-symbol-over-decimal	23
minimum-integer-digits (option)	19	arc-separator	23
\minute	5	bracket-negative	22
\mJ	10	bracket-unit-denominator	24
\mL	9	color	14
\ml	9	drop-exponent	17, 33
\mm	8	drop-uncertainty	17
\mmol	8	drop-zero-decimal	19
\MN	9	evaluate-expression	16
\mN	9	exponent-base	21
mode (option)	13	exponent-mode	16
\Mohm	9	exponent-product	21
\mohm	9	expression	16
\mol	8	fill-arc-degrees	23
\mole	5	fill-arc-minutes	23
\mp	15	fill-arc-seconds	23
\MPa	9	fixed-exponent	16
\ms	8	font-command	26
\multicolumn	11	forbid-literal-units	26
\multirow	11	group-digits	20
\mV	9	group-four-digits	20
\MW	10	group-minimum-digits	20
\mW	10	group-separator	20
		input-close-uncertainty	15
		input-comparators	15
		input-decimal-markers	15
		input-digits	15
		input-exponent-markers	15
		input-ignore	15
		input-open-uncertainty	15
		input-signs	15
		input-uncertainty-signs	15
		inter-unit-product	24
		minimum-decimal-digits	19
		minimum-integer-digits	19
		mode	13
		negative-color	22
		number-angle-product	23
		number-color	14
		number-mode	13
		output-close-uncertainty	21

## N

\N	9
\nA	8
\nano	7
\nauticalmile	6
negative-color (option)	22
\neper	6
\newton	5
\ng	8
\nm	8
\nmol	8
\ns	8
\nuaction	6
\num	2
\num	2, 3, 4
\numass	6
number-angle-product (option)	23

## O

\oersted	6
\of	7
\of	7
\ohm	5
options:	
angle-mode	22
angle-symbol-over-decimal	23
arc-separator	23
bracket-negative	22
bracket-unit-denominator	24
color	14
drop-exponent	17, 33
drop-uncertainty	17
drop-zero-decimal	19
evaluate-expression	16
exponent-base	21
exponent-mode	16
exponent-product	21
expression	16
fill-arc-degrees	23
fill-arc-minutes	23
fill-arc-seconds	23
fixed-exponent	16
font-command	26
forbid-literal-units	26
group-digits	20
group-four-digits	20
group-minimum-digits	20
group-separator	20
input-close-uncertainty	15
input-comparators	15
input-decimal-markers	15
input-digits	15
input-exponent-markers	15
input-ignore	15
input-open-uncertainty	15
input-signs	15
input-uncertainty-signs	15
inter-unit-product	24
minimum-decimal-digits	19
minimum-integer-digits	19
mode	13
negative-color	22
number-angle-product	23
number-color	14
number-mode	13
output-close-uncertainty	21

output-decimal-marker	21	\peta	7
output-open-uncertainty	21	\pF	10
parse-numbers	16, 33	\pg	8
parse-units	26	\phot	6
per-mode	24	\pico	7
per-symbol	24	\pm	7, 8, 15
propagate-math-font	14	\pmol	8
qualifier-mode	26	\poise	6
qualifier-phrase	26	propagate-math-font (option)	14
reset-math-version	14	\ps	8
reset-text-family	13	\pV	9
reset-text-series	13		
reset-text-shape	13		
round-half	18	<b>Q</b>	
round-minimum	19	\qty	4
round-mode	18	\qty	4, 7, 23
round-pad	18	qualifier-mode (option)	26
round-precision	18	qualifier-phrase (option)	26
separate-uncertainty	21		
sticky-per	25	<b>R</b>	
table-align-exponent	30	\radian	5
table-align-text-after	31	\raiseto	7
table-align-text-before	31	\raiseto	7
table-align-uncertainty	30	reset-math-version (option)	14
table-alignment	35, 36	reset-text-family (option)	13
table-auto-round	32	reset-text-series (option)	13
table-column-width	34	reset-text-shape (option)	13
table-fixed-width	34	round-half (option)	18
table-format	28	round-minimum (option)	19
table-mode	27	round-mode (option)	18
table-number-alignment	27	round-pad (option)	18
table-text-alignment	35	round-precision (option)	18
text-family-to-math	14		
text-weight-to-math	14	<b>S</b>	
tight-spacing	22	\s	8
uncertainty-separator	21	\second	5
unit-color	14	separate-uncertainty (option)	21
unit-mode	13	\siemens	5
output-close-uncertainty (option)	21	\sievert	5
output-decimal-marker (option)	21	\sim	15
output-open-uncertainty (option)	21	\square	7
		\square	7
		\squared	7
		\squared	7
		\steradian	5
<b>P</b>		sticky-per (option)	25
\Pa	9	\stilb	6
\pA	8	\stokes	6
parse-numbers (option)	16, 33		
parse-units (option)	26	<b>T</b>	
\pascal	5	table-align-exponent (option)	30
\per	7	table-align-text-after (option)	31
\per	4, 7, 24, 25, 25	table-align-text-before (option)	31
per-mode (option)	24	table-align-uncertainty (option)	30
per-symbol (option)	24	table-alignment (option)	35, 36
\percent	4	table-auto-round (option)	32
\percent	4		

table-column-width (option) . . . . .	34	\um . . . . .	8
table-fixed-width (option) . . . . .	34	\umol . . . . .	8
table-format (option) . . . . .	28	uncertainty-separator (option) . . . . .	21
table-mode (option) . . . . .	27	\unit . . . . .	3
table-number-alignment (option) . . . . .	27	\unit . . . . .	3, 4, 7
table-text-alignment (option) . . . . .	35	unit-color (option) . . . . .	14
\tablenum . . . . .	11	unit-mode (option) . . . . .	13
\tablenum . . . . .	11, 12	\us . . . . .	8
\tera . . . . .	7	\uV . . . . .	9
\tesla . . . . .	5	\uW . . . . .	9
\TeV . . . . .	10		
\text . . . . .	12		
text-family-to-math (option) . . . . .	14	<b>V</b>	
text-weight-to-math (option) . . . . .	14	\V . . . . .	9
\THz . . . . .	9	\volt . . . . .	5
tight-spacing (option) . . . . .	22		
\tonne . . . . .	5	<b>W</b>	
\tothe . . . . .	7	\W . . . . .	9
\tothe . . . . .	7	\watt . . . . .	5
		\weber . . . . .	5
		<b>Y</b>	
<b>U</b>		\yocto . . . . .	7
\uA . . . . .	8	\yotta . . . . .	7
\ug . . . . .	8		
\uJ . . . . .	10		
\uL . . . . .	9	<b>Z</b>	
\ul . . . . .	9	\zepto . . . . .	7
		\zetta . . . . .	7